

## Table of Contents

### Utilization and accounting

Comparison of sreport, sacct, and sshare

Resource accounting uniformization

Conversion Rules extract (see below for details)

Example Calculation

Resources available for research group

Job accounting

OpenXDMoD

sacct

Report and statistics with sreport

Usage details of a given PI

Usage details of all PIs associated with a private group

Aggregate usage by all users of a given PI

sreport examples

# Utilization and accounting

When you submit jobs, they are using physical resources such as CPUs, Memory, Network, GPUs, Energy etc. We keep track of the usage of some of those resource. On this page we'll let you know how to consult your usage of the resource. We have several tools that you can use to consult your utilization: sacct, sreport, openxdmod

## Comparison of sreport, sacct, and sshare

We use **sreport** as our primary accounting reference. However, you may find other tools useful for specific purposes. Here's a comparison:

- **sacct**: Displays only account jobs, excluding time allocated via reservations. If duplicate jobs exist, only one is shown.
- **sreport**: By default, jobs with wall times overlapping the report's time range are truncated. For reservation-based jobs, the requested idle time is distributed among all users with access to the reservation.
- **sshare**: Not recommended for accounting purposes; displayed values are adjusted based on fairshare calculations.

## Resource accounting uniformization

We apply uniform resource accounting by converting GPU hours and memory usage into CPU-hour equivalents, using the [TRESBillingWeights](#) feature provided by SLURM. A CPU hour represents one hour of processing time on a single CPU core.

We use this model because our cluster is heterogeneous, and both the computational power and the cost of GPUs vary significantly depending on the model. To ensure fairness and transparency, each GPU type is assigned a weight that reflects its relative performance compared to a CPU core. Similarly, memory usage is converted into CPU-hour equivalents based on predefined weights.

We also bill memory usage because some jobs consume very little CPU but require large amounts of memory, which means an entire compute node is occupied. This ensures that jobs using significant memory resources are accounted for fairly.

Example: A job using a GPU with a weight of 10 for 2 hours and memory equivalent to 5 CPU hours would be billed as 25 CPU hours. This approach guarantees consistent, transparent, and fair resource accounting across all heterogeneous components of the cluster.

You can check the up to date conversion details by inspecting the parameters of any partition on the clusters. The same conversion table is applied everywhere.

```
(bamboo)-[root@slurm1 ~]$ scontrol show partition debug-cpu | grep
TRESBillingWeights | tr "," "\n"
  TRESBillingWeights=CPU=1.0
Mem=0.25G
GRES/gpu=1
GRES/gpu:nvidia_a100-pcie-40gb=5
GRES/gpu:nvidia_a100_80gb_pcie=8
GRES/gpu:nvidia_geforce_rtx_2080_ti=2
GRES/gpu:nvidia_geforce_rtx_3080=3
GRES/gpu:nvidia_geforce_rtx_3090=5
GRES/gpu:nvidia_geforce_rtx_4090=8
GRES/gpu:nvidia_rtx_a5000=5
GRES/gpu:nvidia_rtx_a5500=5
GRES/gpu:nvidia_rtx_a6000=8
GRES/gpu:nvidia_titan_x=1
GRES/gpu:tesla_p100-pcie-12gb=1
```

Here you can see for example that using a gpu nvidia\_a100-pcie-40gb for 1 hour is equivalent in term of cost to use 5 CPUhour.

## Resources available for research group

Research groups that have invested in the HPC cluster by purchasing private CPU or GPU nodes benefit from high priority access to these resources.

While these nodes remain available to all users, owners receive priority scheduling and a designated number of included compute hours per year named [billings](#)). [To check the details of their owned resources](#), users can run the script "[ug\\_getNodeCharacteristicsSummary.py](#)", which provides a summary of the node characteristics within the cluster. Example: `<code>`

```
ug_getNodeCharacteristicsSummary.py --partitions private-<group>-gpu private-<group>-cpu --
cluster <cluster> --summary host sn cpu mem gpunumber gpudeleted gpumodel gpumemory
purchasedate months remaining in prod. (Jan 2025) billing -----
----- cpu084 N-20.02.151 36 187 0 0
0 2020-02-01 1 79 cpu085 N-20.02.152 36 187 0 0 0 2020-02-01 1 79 cpu086 N-20.02.153 36 187 0 0
0 2020-02-01 1 79 cpu087 N-20.02.154 36 187 0 0 0 2020-02-01 1 79 cpu088 N-20.02.155 36 187 0 0
0 2020-02-01 1 79 [...] cpu226 N-19.01.161 20 94 0 0 0 2019-01-01 0 41 [...] cpu229 N-19.01.164 20
94 0 0 0 2019-01-01 0 41 cpu277 N-20.11.131 128 503 0 0 0 2020-11-01 10 251 gpu002 S-16.12.215
12 251 5 0 NVIDIA TITAN X (Pascal) 12288 2016-12-01 0 84 gpu012 S-16.12.216 24 251 8 0 NVIDIA
```

```

GeForce RTX 2080 Ti 11264 2016-12-01 0 108 gpu017 S-20.11.146 128 503 8 0 NVIDIA GeForce RTX
3090 24576 2020-11-01 10 299 gpu023 S-21.09.121 128 503 8 0 NVIDIA GeForce RTX 3080 10240
2021-09-01 20 283 gpu024 S-21.09.122 128 503 8 0 NVIDIA GeForce RTX 3080 10240 2021-09-01 20
283 gpu044 S-23.01.148 128 503 8 0 NVIDIA RTX A5000 24564 2023-01-01 36 299 gpu047
S-23.12.113 128 503 8 0 NVIDIA RTX A5000 24564 2023-12-01 47 299 gpu049 S-24.10.140 128 384 8
0 NVIDIA GeForce RTX 4090 24564 2024-10-01 57 291

```

Summary

```

Total CPUs: 1364 Total CPUs memory[GB]: 6059 Total GPUs: 61 Total GPUs memory[MB]: 142300
Billing: 1959 CPUhours per year: 10.30M

```

How to read the output: **host**: the hostname of the compute node **sn**: the serial number of the node **cpu**: the number of CPUs available in the node **mem**: the quantity of memory on the node in GB **gpunumber**: the number of GPU cards on the node **gpudeleted**: the number of GPU cards out of order **gpumodel**: the GPU model **gpumemory**: the GPU memory in MB per GPU card **purchasedate**: the purchase date of the node **months remaining in prod. (Jan 2025)**: the number of months the node remains the property of the research group, the reference date is indicated in parenthesis. In this example it is January 2025. **billing**: the `[[hpc:accounting#resource_accounting_uniformization|billing` value of the compute node

You can modify the reference year if you want to “simulate” the hardware you'll have in your private partition in a given year. To do so, use the argument `--reference-year` of the script.

## Job accounting

### OpenXDMoD

We track the job usage of our clusters here: <https://openxdmod.hpc.unige.ch/>

We have a tutorial explaining some of the features: [here](#)

Openxdmod is integrated into our SI. When you connect to it, you'll get the profile “user” and the data are filtered by your user by default. If you are a PI, you can ask us to change your profile to be PI.



OpenXDMoD currently supports only CPUh and GPUh metrics, not the **billing** metrics (yet?). For this reason, you need to use [sreport](#) or [our script](#) if you want to view the billed metrics.

### sacct

You can see your job history using `sacct`:

```

[sagon@master ~] $ sacct -u $USER -S 2021-04-01
  JobID      JobName      Partition      Account      AllocCPUS      State      ExitCode
-----
45517641     jobname      debug-cpu      rosigno             1      FAILED      2:0

```

45517641.ba+	batch		rossigno	1	FAILED	2:0
45517641.ex+	extern		rossigno	1	COMPLETED	0:0
45517641.0	R		rossigno	1	FAILED	2:0
45518119	jobname	debug-cpu	rossigno	1	COMPLETED	0:0
45518119.ba+	batch		rossigno	1	COMPLETED	0:0
45518119.ex+	extern		rossigno	1	COMPLETED	0:0

## Report and statistics with sreport

To get reporting about your past jobs, you can use `sreport` (<https://slurm.schedmd.com/sreport.html>).

We wrote a helper that you can use to get your past resource usage on the cluster. This script can display the resource utilization

- for each user of a given account (PI)
- total usage of a given account (PI)

```
(baobab) - [sagon@login1 ~]$ ug_slurm_usage_per_user.py -h
usage: ug_slurm_usage_per_user.py [-h] [--user USER] [--start START] [--end
END] [--pi PI] [--group GROUP] [--cluster {baobab,yggdrasil,bamboo}] [--
all_users] [--report_type {user,account}] [--time_format
{Hours,Minutes,Seconds}]
                                [--verbose]
```

Retrieve HPC utilization statistics for a user or group of users.

options:

```
-h, --help                show this help message and exit
--user USER              Username to retrieve usage for.
--start START            Start date (default: first of month).
--end END                End date (default: now).
--pi PI                  Specify a PI manually.
--group GROUP            Specify a group name to get all PIs belonging to it.
--cluster {baobab,yggdrasil,bamboo}
                          Cluster name (default: all clusters).
--all_users              Include all users under the PI account.
--report_type {user,account}
                          Type of report: user (default) or account.
--time_format {Hours,Minutes,Seconds}
                          Time format: Hours (default), Minutes, or Seconds.
--verbose                Verbose output.
```

By default when you run this script, it will print your past usage of the current month, for all the accounts you are member of.

Usage example to see the resource usage from the beginning of 2025 for all the PIs and associate users of the group `private_xxx`. The group `private_xxx` owns several compute nodes:

```
(baobab) - [sagon@login1 ~]$ ug_slurm_usage_per_user.py --group private_xxx --
```

```

start=2025-01-01 --report_type=account
-----
----
Cluster/Account/User Utilization 2025-01-01T00:00:00 - 2025-08-21T14:59:59
(20095200 secs)

Usage reported in TRES Hours
-----
----
Cluster      Login      Proper Name  Account    TRES Name    Used
-----
baobab       PI1       billing      56134
yggdrasil    PI1       billing      105817
bamboo       PI2       billing      5416
baobab       PI2       billing      1517001
yggdrasil    PI2       billing      23775
bamboo       PI3       billing      0
baobab       PI3       billing      1687963
yggdrasil    PI3       billing      1344599
[...]
Total usage: 7.36M

```

### sreport examples

Here are some examples that can give you a starting point :

To get the number of jobs you ran (you ⇔ \$USER) in 2018 (dates in yyyy-mm-dd format) :

```

[brero@login2 ~]$ sreport job sizesbyaccount user=$USER PrintJobCount
start=2018-01-01 end=2019-01-01
-----
----
Job Sizes 2018-01-01T00:00:00 - 2018-12-31T23:59:59 (31536000 secs)
Units are in number of jobs ran
-----
----
Cluster      Account    0-49 CPUs  50-249 CPUs  250-499 CPUs  500-999 CPUs
>= 1000 CPUs % of cluster
-----
baobab       root      180         40           4             15
0           100.00%

```

You can see how many jobs were run (grouped by allocated CPU). You can also see we specified an extra day for the *end date* end=2019-01-01 in order to cover the whole year :

Job Sizes 2018-01-01T00:00:00 - 2018-12-31T23:59:59 ' '

You can also check how much CPU time (seconds) you have used on the cluster between since 2019-09-01 :

```
[brero@login2 ~]$ sreport cluster AccountUtilizationByUser user=$USER
start=2019-09-01 -t Seconds
-----
----
Cluster/Account/User Utilization 2019-09-01T00:00:00 - 2019-09-09T23:59:59
(64800 secs)
Usage reported in CPU Seconds
-----
-----
Cluster      Account      Login      Proper Name      Used      Energy
-----
baobab      rosigno      brero      BRERO Massimo    1159      0
```

In this example, we added the time -t Seconds parameter to have the output in seconds. Minutes or Hours are also possible.

Please note :

- By default, the CPU time is in Minutes
- It takes up to an hour for Slurm to update this information in its database, so be patient
- If you don't specify a start, nor an end date, yesterday's date will be used.
- The CPU time is the time that was allocated to you. It doesn't matter if the CPU was actually used or not. So let's say you ask for 15min allocation, then do nothing for 3 minutes then run 1 CPU at 100% for 4 minutes and exit the allocation, then 7 minutes will be added to your CPU time.

Tip : If you absolutely need a report including your job that ran on the same day, you can override the default end date by forcing tomorrow's date :

```
sreport cluster AccountUtilizationByUser user=$USER start=2019-09-01
end=$(date --date="tomorrow" +%Y-%m-%d) -t seconds
```

From: <https://doc.eresearch.unige.ch/> - **eResearch Doc**

Permanent link: <https://doc.eresearch.unige.ch/hpc/accounting?rev=1764844147>

Last update: **2025/12/04 10:29**

